# **843WD CLAMSHELL LATHE**

### MACTECH PORTABLE MACHINING SOLUTIONS

# **Features**

- Sever or simultaneous Sever/Bevel
   31 to 43 inch diameter pipe, or NPS 32 to
   NPS 42 schedule pipe.
- Cold cutting in hazardous environments.
- Exceptionally rigid, split-frame for precise on-site machining.
- Lightweight, low clearance design for easy handling in tight working spaces.
- Tool Holder accepts standard 3/4 or 1 inch tool bits.
- Air Caddy (air filter and oiler) included with air drive systems.
- Custom setups and drives available for your application.

# Split Line Tool Block Drive Drive Motor Tripper Pins

Tool Block

Mactech 843WD Clamshell Lathe

### 843WD Nominal Pipe Size (NPS) Application Range

Nominal Pipe Size (in.)	Schedule No.	Wall Thickness (in.)	Inside Diameter (in.)
32 (32.000)	10 ST 20 30 40	0.312 0.375 0.500 0.625 0.688	31.376 31.250 31.000 30.750 30.624
34 (34.000)	10 ST 20 30 40	0.312 0.375 0.500 0.625 0.688	33.376 33.250 33.000 32.750 32.624

Nominal Pipe Size (in.)	Schedule No.	Wall Thickness (in.)	Inside Diameter (in.)
36 (36.000)	10 ST, 40S XS, 80S	0.312 0.375 0.500	35.375 35.250 35.000
42 (42.000)	ST, 40S XS, 80S 30 40	0.375 0.500 0.625 0.750	41.250 41.000 40.750 40.500

# **Options**

- · Full line of tool bits
- · Right angle and reversible drives
- · Single Point machining attachment
- Axial Feed machining attachment
- Counterbore/Facing attachment
- Hydraulic Power Unit

# **Application Range**

31.00 to 43.00 inch (787 to 1092 mm) diameter pipe, or NPS 32 to NPS 42 schedule pipe.

### **Feed**

Feed Mechanism: 4 point starwheel with 3-pin tripper feed. Feed Rate: .002, .004 or .006 inches per revolution (0.05, 0.11 or 0.16 mm).

### **Drives**

Air Drive

Air supply requirement: 100 cfm @100 psi (2.8 m³/min @ 6.9 bar)

**Hydraulic Drive** 

HPU requirement: 10-15 gpm @ 1000 psi (38-57 lpm @ 69 bar) continuous pressure Hydraulic motor includes hose whips and quick-disconnects

Weights (includes tool blocks and motor)

Operating Weights

843WD Air Drive: 695 lbs. (315 kg) 843WD Hydraulic Drive: 707 lbs. (321 kg)

Shipping Weights

843WD Air Drive: 1100 lbs. (499 kg) 843WD Hydraulic Drive: 1112 lbs. (504 kg)



# **843WD CLAMSHELL LATHE**

# MACTECH PORTABLE MACHINING SOLUTIONS





